



## Merkmale / Features

- D** • Y-Schmutzfänger Flansch  
 • Flanschanschluss PN16/PN40, EN 1092-B1  
 • Baulänge nach EN 558-1 Reihe 1  
 • Temperaturbereich: -10°C bis +400°C  
 • PED2014/68/EU, Annex III, Module H  
 • AD2000 A4  
 • Test EN 12266

- E** • Flanged Y-type Strainer  
 • Flanged connection PN16/PN40, EN 1092-B1  
 • Face to face according to EN 558-1, Line 1  
 • Temperature range: -10°C upto +400°C  
 • PED2014/68/EU, Annex III, Module H  
 • AD2000 A4  
 • Test EN 12266

## Werkstoff / Materials

Nr.	Bauteil/Part	Werkstoff/Material
1	Bolzen / Bolt	Gr 8.8
2	Dichtungsring / Sealing piece	Cu Alloy
3	Schraube / Screw	C22.8
4	Deckel / Cover	A105
5	Dichtung / Gasket	Graphite + SS304
6	Sieb / Screen	SS304
7	Gehäuse / Body	1.0619

## Abmessungen / Dimensions [mm]

DN	L	D		D1		D2		B		f	N - Ø		H	Kv	A-C	M
		PN16	PN40	PN16	PN40	PN16	PN40	PN16	PN40		PN16	PN40				
15	130	95	95	65	65	45	45	16	16	2	4x14	4x14	70	7	45*35	M16*1,5
20	150	105	105	75	75	58	58	18	18	2	4x14	4x14	85	11	50*40	M16*1,5
25	160	115	115	85	85	68	68	18	18	2	4x14	4x14	98	18	55*45	M16*1,5
32	180	140	140	100	100	78	78	18	18	2	4x18	4x18	105	26	60*50	M16*1,5
40	200	150	150	110	110	88	88	18	18	3	4x18	4x18	125	37	75*65	M27*2
50	230	165	165	125	125	102	102	20	20	3	4x18	4x18	135	60	85*75	M27*2
65	290	185	185	145	145	122	122	18	22	3	4x18	8x18	157	100	105*90	M27*2
80	310	200	200	160	160	138	138	20	24	3	8x18	8x18	180	150	125*110	M27*2
100	350	220	235	180	190	158	162	20	24	3	8x18	8x22	230	230	145*130	M33*2
125	400	250	270	210	220	188	188	22	26	3	8x18	8x26	277	330	170*155	M33*2
150	480	285	300	240	250	212	218	22	28	3	8x22	8x26	325	400	210*190	M33*2
200	600	340	375	295	320	268	285	24	34	3	12x22	12x30	410	650	260*235	M33*2
250	730	405	450	355	385	320	345	26	38	3	12x26	12x33	515	1200	330*305	M33*2
300	850	460	515	410	450	378	410	28	42	4	12x26	16x33	615	1900	385*360	M33*2
350	980	520	580	470	510	438	465	30	46	4	16x26	16x36	675	2580	435*410	M33*2
400	1100	580	660	525	585	490	535	32	50	4	16x30	16x39	780	3345	490*465	M33*2